

# Excel 12 Way Vertical PDU 12x Schuko Socket Passive 16A Schuko Plug LED

Part Code: 555-086

sales@excel-networking.com  
excel-networking.com

CIBSE TM65 Embodied Carbon: 12.624 kg CO2e



## Main Features

- / High quality aluminium housing
- / LED indicator
- / 250 volt AC, 50/60Hz Rating
- / Switched and unswitched options
- / 3 metre PVC input lead terminated with 2 pin DIN49441 plug
- / CE safety compliant, RoHS compliant

## Product Overview

Excel range of power distribution units are designed for installation and use within 19" networking cabinets and enclosures. Each unit comprises a high quality aluminium extruded housing into which are loaded up to 12 sockets. In this particular range each socket is 'Schuko' style, manufactured in accordance with the DIN49441 standard, the 3 metre input lead is terminated with a 16AMP rated 2 time circular pin DIN49441 plug top.

The range of available units includes 19" vertically mounted, higher density vertical mounted options, and a choice of styles with and without switches to control input power to the unit itself.

The unswitched versions have a LED indicator to confirm power to the unit, in the switched versions the switch itself acts as the LED indicator.

# Excel 12 Way Vertical PDU 12x Schuko Socket Passive 16A Schuko Plug LED

Part Code: 555-086

sales@excel-networking.com  
excel-networking.com

## Product Specifications

Feature	Values
Mounting dimension	19 inch
Mounting size	624.5 mm
Mounting direction	Vertical
Electrical connection	Connecting cord with plug
Type of electric plug connection	2 Pin DIN49441
Cable length	3 m
Number of Schuko socket outlets	12
Width	44.4 mm
Height	651 mm
Depth	62 mm
Supply voltage	250 V
Switchable	no
With LED indication	no
With mounting bracket	yes

## Additional specifications

Features	Values
Input cable type	3 core 1.5mm cable
PDU Input cable connector	N/A
Rated Voltage	250 V AC 50/60 Hz
Rated current	16 Amp


# Excel 12 Way Vertical PDU 12x Schuko Socket Passive 16A Schuko Plug LED

Part Code: 555-086

sales@excel-networking.com  
excel-networking.com

Maximum power	<b>4000 W</b>
Unit control	<b>LED indicator. On/off rocker switch</b>
Insulation Resistance	<b>≥5MΩ</b>
Fire resistance	<b>Flame retardant</b>
Operating temperature	<b>-10°C to +45°C</b>
Relative humidity	<b>0% to 90%</b>
Cable entry (horizontal orientation)	<b>Left</b>
Cable entry (vertical orientation)	<b>Top</b>
Master Circuit Breaker	<b>NO</b>
Master Switch	<b>Yes (only on products marked as 'Switched')</b>
Housing colour	<b>Silver</b>
Housing material	<b>Aluminum</b>

## Product drawing



Key	
A	Height
B	Width
C	Depth
D	Mounting Centres

All dimensions are in mm unless stated otherwise

# Excel 12 Way Vertical PDU 12x Schuko Socket Passive 16A Schuko Plug LED

Part Code: 555-086

sales@excel-networking.com  
excel-networking.com

## Standards

Applicable standard	Detail
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
DIN VDE 0620-2-1:2016	Plugs and socket-outlets for household and similar purposes
DIN 49441	Two-pole Plugs with Earthing Contact 10 A 250 V $\approx$ AND 10 A 250 V $\square$ , 16 A 250 V $\sim$
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

# Excel 12 Way Vertical PDU 12x Schuko Socket Passive 16A Schuko Plug LED

Part Code: 555-086

sales@excel-networking.com  
excel-networking.com

## Included accessories

Accessories	Quantity
M6 x 4 fixings	x4
user manual	x1
6mm earth cable	x1

## Part Code Table

Part Code	Description
555-072	Excel 6 Way Horizontal PDU 6x Schuko Socket Passive 16A Schuko Plug Switched
555-073	Excel 8 Way Vertical PDU 8x Schuko Socket Passive 16A Schuko Plug Switched
555-082	Excel 6 Way Horizontal PDU 6x Schuko Socket Passive 16A Schuko Plug LED
555-083	Excel 8 Way Vertical PDU 8x Schuko Socket Passive 16A Schuko Plug LED
555-084	Excel 9 Way Vertical PDU 9x Schuko Socket Passive 16A Schuko Plug LED
555-086	Excel 12 Way Vertical PDU 12x Schuko Socket Passive 16A Schuko Plug LED