Elevate 1P Vertical Int PDU (INT1) 12x C13 4x C19 Socket 16 A EN60309 3 m Top-fed

Part Code: 555-1V-COM16-INT1-12C13-4C19-3T

sales@excel-networking.com
excel-networking.com



Main Features

/ Monitors overall energy usage with a local color LCD display.

/ Scalable: link up to 31 units from a single master PDU.

/ Mounting options: horizontal and vertical for flexible placement.

/ Free embedded software for remote monitoring via web interface.

/ Variety of sockets: choose from UK, Schuko, C13, and C19.

/ Optional environmental sensors: temperature, humidity, and door contact.

Product Overview

The Elevate INT1 Intelligent PDU is a UK-manufactured energy monitoring PDU that provides local and remote overall power monitoring with high accuracy. Offered in various configurations, the INT1 comes standard with C13 and C19 sockets powered by EN60309 Com16 or Com32 plugs, in single or three-phase options. The INT1 offers flexibility with a maximum of 48 sockets. Standard options include C13, C19, UK, UK left-angled and right-angled, and Schuko socket types.

The INT1 features environmental ports for temperature, humidity sensors, water detection rope, or door sensors. It can also integrate with electronic access control handles for your data centre racks. For larger deployments, daisy-chain up to 32 devices using a single master PDU with a single IP address. The included free software allows remote monitoring via a user-friendly HTML browser with secure login.

This data sheet was generated at 5:56am 4th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

The INT1 features an RGB backlit LCD display for real-time power usage across all connected devices. Additionally, configure SNMP and email alerts for critical parameters like voltage, current, power factor, and internal temperature. With over 1% accuracy, the INT1 measures RMS volts, amps, kilowatts, frequency, power factor, internal PDU temperature, peak volts and amps, kVA, and kWh.

Product Specifications

Feature	Values
Mounting direction	**Vertical**
Electrical connection	**Connecting cord with plug**
Type of electric plug connection	**16 Amp - EN6039 Style (BS4343)**
Cable length	**3 m**
Number of C13 socket outlets	**12**
Number of C19 socket outlets	**4**
Supply voltage	**230 V**
Surge Protected	**no**
Switchable	**no**
SNMP	**yes**
Display	**yes**
Evaluation	**Remote**
With LED indication	**yes**
With fuse	**yes**
Ammeter	**yes**
With temperature measurement	**yes**
With mounting bracket	**yes**

This data sheet was generated at 5:56am 4th November 2026 and is subject to change at any time.

sales@excel-networking.com
excel-networking.com

Part Code Table

Part Code	Description
555-1V-COM16-INT1-12C13-4C19-3T	**Elevate VT 1P PDU 12xC13 4xC19 INT1 16A Comm 3m TF**

This data sheet was generated at 5:56am 4th November 2026 and is subject to change at any time.