

Elevate 1P Vertical Intelligent PDU (INT3) 12x C13 4x C19 Socket 16A EN60309 3m Bottom Fed

Part Code: 555-1V-COM16-INT3-12C13-4C19-3B

sales@excel-networking.com
excel-networking.com



Main Features

- / Individual socket monitoring and remote switching
- / Local color LCD display with RGB backlight
- / Free embedded software for remote management (up to 31 units)
- / Choice of UK, Schuko, C13 & C19 sockets
- / Horizontal & vertical mounting options
- / Available in single-phase or three-phase configurations

Product Overview

The Excel INT3 Intelligent PDU is a UK manufactured energy monitoring PDU. It provides local and remote overall power monitoring with a high degree of accuracy along with individual socket monitoring and remote switching capabilities. The Excel INT3 PDUs come as standard with C13 and C19 sockets powered by EN60309 Com16 or Com32 plugs in various combinations, available in both single-phase and three-phase configurations. They can also be equipped with other socket types, including UK, angled UK (left or right), or Schuko sockets, for a maximum of 48 sockets per unit. The Excel Intelligent PDUs also feature environmental ports for connecting temperature and humidity sensors, water detection cables, or door sensors. They can even be linked to electronic access control handles on your data center racks. For multi-unit deployments, PDUs can be daisy-chained with up to 32 devices monitored from a single IP address using a master PDU. This master...

Elevate 1P Vertical Intelligent PDU (INT3) 12x C13 4x C19 Socket 16A EN60309 3m Bottom Fed

Part Code: 555-1V-COM16-INT3-12C13-4C19-3B

sales@excel-networking.com
excel-networking.com

Product Specifications

Feature	Values
Mounting direction	Vertical
Electrical connection	Connecting cord with plug
Type of electric plug connection	16 Amp - EN6039 Style (BS4343)
Cable length	3 m
Number of C13 socket outlets	12
Number of C19 socket outlets	4
Supply voltage	230 V
Surge Protected	no
Switchable	no
SNMP	yes
Display	yes
Evaluation	Remote
With LED indication	yes
With fuse	yes
Ammeter	yes
With temperature measurement	yes
With mounting bracket	yes

Elevate 1P Vertical Intelligent PDU (INT3) 12x C13 4x C19 Socket 16A EN60309 3m Bottom Fed

Part Code: 555-1V-COM16-INT3-12C13-4C19-3B

sales@excel-networking.com
excel-networking.com

Additional specifications

Features	Values
Technology	Overall + individual socket monitoring + switching
Energy Metering	RMS Volts, RMS Amps, Kilowatts, Frequency, Power Factor
Metering per Input Line	Yes (overall and individual)
Metering per Output Receptacle	Yes
Remote Outlet Switching	Yes
Environmental port	Yes
Networking	SNMP (v1, 2, 3), HTML, HTTP, HTTPs, XML, Email Alerts
Remote Management	Yes
Daisy Chain	Yes (1 Master up to 31 Slaves)
Display	Local (remote display optional)
Environmental Sensors	Temperature Sensor Port (Up to 8 Sensors), Humidity / Temperature Sensor, Volt Free Contacts (3 Sets), Door Contacts, Electronic Door Handle, Card Reader / Pin Pads
Frequency	50 - 60 Hz
Main Input	85 - 265 VAC
Colour	Black (standard) - other colours available
Temperature Range	-10^o to +50^o C

Elevate 1P Vertical Intelligent PDU (INT3) 12x C13 4x C19 Socket 16A EN60309 3m Bottom Fed

Part Code: 555-1V-COM16-INT3-12C13-4C19-3B

sales@excel-networking.com
excel-networking.com

Socket types



Schuko



3 Pin - BS1363



BS1363
& C13 - IEC60320



C13 - IEC60320



C19 - IEC60320

Standards

Applicable standard	Detail
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
IEC 60950-1	Information technology equipment - Safety
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).

Elevate 1P Vertical Intelligent PDU (INT3) 12x C13 4x C19 Socket 16A EN60309 3m Bottom Fed

Part Code: 555-1V-COM16-INT3-12C13-4C19-3B

sales@excel-networking.com
excel-networking.com

UKSI 2012 No. 3032

The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Code Table

Part Code	Description
555-1V-COM16-INT3-12C13-4C19-3B	Elevate 1P Vertical Intelligent PDU (INT3) 12x C13 4x C19 Socket 16A EN60309 3m Bottom Fed
555-1V-COM32-INT3-20SCH-XXX-3B	Excel 1P Vert Int PDU (INT3) 20x Schuko Socket 32A EN60309 3m Bottom-fed
555-1V-COM32-INT3-20UKL-XXX-3B	Excel 1P Vert Int PDU (INT3) 20x UK Left Socket 32A EN60309 3m Bottom-fed