

Excel Single-phase Vertical Intelligent PDU (INT2) c/w 20x C13, 4x C19 sockets - 32A EN60309 3m...



Item Code: 555-1V-COM32-INT2-20C13-4C19-3B



Monitors overall voltage

Local display via the RGB

Embedded free software

Link up to 31 units from single IP address

Choice of UK, Schuko, C13 and C19 socket types

Horizontal and vertical options

Optional sensors ? temperature, humidity, door

Product Overview

The Excel Intelligent INT2 is designed to provide local and remote overall power monitoring and is available with up to 48 sockets with any combination of socket type including UK, Schuko, C13, C19 etc.

The Excel Intelligent INT2 can work as an individual master or run as a master and slave system. One master can have up to 31 slaves, all from one IP address, reducing the requirement for multiple IP addresses.

The Excel Intelligent INT2 comes with free software making it a highly competitive solution allowing the user to monitor and report on up to 50 IP addresses with the software. In theory it is possible to have up to 1600 PDU's each with up to 48 outlets per PDU, all from one free software licence.

Product Specifications

Feature	Values
Mounting direction	Vertical
Type of electric plug connection	32 Amp - EN6039 Style (BS4343)
Cable length	3 m
Number of C13 socket outlets	20
Number of C19 socket outlets	4
Surge Protected	no
Switchable	no

Excel Single-phase Vertical Intelligent PDU (INT2) c/w 20x C13, 4x C19 sockets - 32A EN60309 3m...



Item Code: 555-1V-COM32-INT2-20C13-4C19-3B

SNMP	yes
Display	yes
Evaluation	Remote
With LED indication	yes
With fuse	yes
Ammeter	yes
With temperature measurement	yes
With mounting bracket	yes

Additional specifications

Features	Values
Technology	Overall + individual socket monitoring
Energy Metering	RMS Volts, RMS Amps, Kilowatts, Frequency, Power Factor
Metering per Input Line	Yes (overall and individual)
Metering per Output Receptacle	Yes
Remote Outlet Switching	No
Environmental port	Yes
Networking	SNMP (v1, 2, 3), HTML, HTTP, HTTPS, XML, Email Alerts
Remote Management	Yes
Daisy Chain	Yes (1 Master up to 31 Slaves)
Display	Local (remote display optional)
Environmental Sensors	Temperature Sensor Port (Up to 8 Sensors), Humidity / Temperature Sensor, Volt Free Contacts (3 Sets), Door Contacts, Electronic Door Handle, Card Reader / Pin Pads
Frequency	50 - 60 Hz
Main Input	85 - 265 VAC
Colour	Black (standard) - other colours available
Temperature Range	-10° to +50° C

Socket types



Standards

Applicable standard	Detail
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
IEC 60950-1	Information technology equipment - Safety
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Excel Single-phase Vertical Intelligent PDU (INT2) c/w 20x C13, 4x C19 sockets - 32A EN60309 3m...



Item Code: 555-1V-COM32-INT2-20C13-4C19-3B

Part Number Table

Part Number	Description
555-1V-COM32-INT2-20C13-4C19-3B	Excel Single-phase Vertical Intelligent PDU (INT2) c/w 20x C13, 4x C19 sockets - 32A EN60309 3m Bottom-fed lead
555-3V-COM32-INT2-18C13-6C19-3T	Excel Three-phase Vertical Intelligent PDU (INT2) c/w 18x C13, 6x C19 sockets - 32A EN60309 3m Top-fed lead
555-3V-COM32-INT2-9C13-3C19-3T	Excel Three-phase Vertical Intelligent PDU (INT2) c/w 9x C13, 3x C19 sockets - 32A EN60309 3m Top-fed lead

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.