

# Elevate 1P Vertical Int PDU (INT3) 16x C13 4x C19 Socket 32 A EN60309 3 m Bottom-fed

Item Code: 555-1V-COM32-INT3-16C13-4C19-3B



Individual socket monitoring and remote switching

Local color LCD display with RGB backlight

Free embedded software for remote management  
(up to 31 units)

Choice of UK, Schuko, C13 & C19 sockets

Horizontal & vertical mounting options

Available in single-phase or three-phase  
configurations

Optional sensors: temperature, humidity, door  
contacts & SNMP/email alerts

## Product Overview

The Elevate INT3 Intelligent PDU is a UK manufactured energy monitoring PDU. It provides local and remote overall power monitoring with a high degree of accuracy along with individual socket monitoring and remote switching capabilities.

The Elevate INT3 PDUs come as standard with C13 and C19 sockets powered by EN60309 Com16 or Com32 plugs in various combinations, available in both single-phase and three-phase configurations.

They can also be equipped with other socket types, including UK, angled UK (left or right), or Schuko sockets, for a maximum of 48 sockets per unit.

The Elevate Intelligent PDUs also feature environmental ports for connecting temperature and humidity sensors, water detection cables, or door sensors. They can even be linked to electronic access control handles on your data center racks.

For multi-unit deployments, PDUs can be daisy-chained with up to 32 devices monitored from a single IP address using a master PDU. This master comes with free software, allowing remote monitoring via a user-friendly HTML browser interface with secure login.

All PDUs are fitted with an RGB backlight LCD display, providing real-time power usage across all connected devices. You can also set up SNMP and email alerts for critical parameters to ensure proactive monitoring.

## Product Specifications

Feature	Values
Mounting direction	Vertical

# Elevate 1P Vertical Int PDU (INT3) 16x C13 4x C19 Socket 32 A EN60309 3 m Bottom-fed

Item Code: 555-1V-COM32-INT3-16C13-4C19-3B



Type of electric plug connection	32 Amp - EN6039 Style (BS4343)
Cable length	3 m
Number of C13 socket outlets	16
Number of C19 socket outlets	4
SNMP	yes
Display	yes
Evaluation	Remote
With mounting bracket	yes

## Part Number Table

Part Number	Description
555-1V-COM32-INT3-16C13-4C19-3B	Excel VT 1P PDU 16xC13 4xC19 INT3 32A Comm 3 m BF

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at [sales@excel-networking.com](mailto:sales@excel-networking.com)



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.