



✗ Choice of C13 and C19 sockets

✗ 3 metre PVC input lead is terminated with a 32 Amp rated IEC 60309 2P+E plug

✗ CE compliant, RoHS compliant

✗ 32A Master air circuit breaker

✗ External earth facility

✗ CIBSE TM65 Embodied Carbon: 37.382 kg CO2e

Product Overview

Excel range of power distribution units are designed for installation and use within 19" networking cabinets and enclosures. Each unit comprises a high quality aluminium extruded housing into which are loaded up to 24 sockets.

The range of units are higher density vertical mounted with each unit fitted with a 32A master air circuit breaker and LED indicator to confirm power to the unit.

Product Specifications

Feature	Values
Mounting direction	Vertical
Electrical connection	Connecting cord with plug
Type of electric plug connection	32 Amp - EN6039 Style (BS4343)
Cable length	3 m
Number of C13 socket outlets	20
Number of C19 socket outlets	4
Length	1375 mm
Width	44.4 mm
Height	62 mm
Supply voltage	230 V

Excel 24 Way Vertical PDU 20x C13 4x C19 Socket Passive 32A IEC 60309 Plug

Item Code: 555-232



Surge Protected	yes
With LED indication	yes
With mounting bracket	yes

Standards

Applicable standard	Detail
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
BS 1363-2:2023	13 A plugs, socket outlets, adaptors and connection units. Part 2: 13 A switched and unswitched socket-outlets - Specification
IEC 60884-1:2002 + AMD1:2006 + AMD2:2013 CSV	Plugs and socket-outlets for household and similar purposes - Part1: General requirements
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
555-230	Excel 16 Way Vertical PDU 12x C13 4x C19 Socket Passive 32A IEC 60309 Plug
555-231	Excel 20 Way Vertical PDU 16x C13 4x C19 Socket Passive 32A IEC 60309 Plug
555-232	Excel 24 Way Vertical PDU 20x C13 4x C19 Socket Passive 32A IEC 60309 Plug

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.

