

Excel Three-phase Vertical Intelligent PDU (INT2)
c/w 9x C13, 3x C19 sockets - 32A EN60309 3m T...



Item Code: 555-3V-COM32-INT2-9C13-3C19-3T



- ✕ Monitors overall voltage
- ✕ Local display via the RGB
- ✕ Embedded free software
- ✕ Link up to 31 units from single IP address
- ✕ Choice of UK, Schuko, C13 and C19 socket types
- ✕ Horizontal and vertical options
- ✕ Optional sensors ? temperature, humidity, door

Product Overview

The Excel Intelligent INT2 is designed to provide local and remote overall power monitoring and is available with up to 48 sockets with any combination of socket type including UK, Schuko, C13, C19 etc.

The Excel Intelligent INT2 can work as an individual master or run as a master and slave system. One master can have up to 31 slaves, all from one IP address, reducing the requirement for multiple IP addresses.

The Excel Intelligent INT2 comes with free software making it a highly competitive solution allowing the user to monitor and report on up to 50 IP addresses with the software. In theory it is possible to have up to 1600 PDU's each with up to 48 outlets per PDU, all from one free software licence.

Product Specifications

Feature	Values
Mounting direction	Vertical
Type of electric plug connection	32 Amp - EN6039 Style (BS4343)
Cable length	3 m
Number of C13 socket outlets	9
Number of C19 socket outlets	3

Excel Three-phase Vertical Intelligent PDU (INT2) c/w 9x C13, 3x C19 sockets - 32A EN60309 3m T...



Item Code: 555-3V-COM32-INT2-9C13-3C19-3T

Surge Protected	no
Switchable	no
SNMP	yes
Display	yes
Evaluation	Remote
With LED indication	yes
With fuse	yes
Ammeter	yes
With temperature measurement	yes
With mounting bracket	yes

Additional specifications

Features	Values
Technology	Overall + individual socket monitoring
Energy Metering	RMS Volts, RMS Amps, Kilowatts, Frequency, Power Factor
Metering per Input Line	Yes (overall and individual)
Metering per Output Receptacle	Yes
Remote Outlet Switching	No
Environmental port	Yes
Networking	SNMP (v1, 2, 3), HTML, HTTP, HTTPS, XML, Email Alerts
Remote Management	Yes
Daisy Chain	Yes (1 Master up to 31 Slaves)
Display	Local (remote display optional)
Environmental Sensors	Temperature Sensor Port (Up to 8 Sensors), Humidity / Temperature Sensor, Volt Free Contacts (3 Sets), Door Contacts, Electronic Door Handle, Card Reader / Pin Pads
Frequency	50 - 60 Hz
Main Input	85 - 265 VAC
Colour	Black (standard) - other colours available
Temperature Range	-10° to +50° C

Excel Three-phase Vertical Intelligent PDU (INT2) c/w 9x C13, 3x C19 sockets - 32A EN60309 3m T...



Item Code: 555-3V-COM32-INT2-9C13-3C19-3T

Socket types



Standards

Applicable standard	Detail
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
IEC 60950-1	Information technology equipment - Safety
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
555-1V-COM32-INT2-20C13-4C19-3B	Excel Single-phase Vertical Intelligent PDU (INT2) c/w 20x C13, 4x C19 sockets - 32A EN60309 3m Bottom-fed lead
555-3V-COM32-INT2-18C13-6C19-3T	Excel Three-phase Vertical Intelligent PDU (INT2) c/w 18x C13, 6x C19 sockets - 32A EN60309 3m Top-fed lead
555-3V-COM32-INT2-9C13-3C19-3T	Excel Three-phase Vertical Intelligent PDU (INT2) c/w 9x C13, 3x C19 sockets - 32A EN60309 3m Top-fed lead

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.