

Excel Intelligent PDU Temperature Sensor Kit with 3 m Lead

Item Code: 555-500-100

excel
without compromise.



- ☒ Monitors temperature variations
- ☒ Separate Min/Max thresholds per sensor
- ☒ Ability to place sensors within the room or cabinet

Product Overview

Housed in Black ABS Enclosures, the IPT Sensors offer accurate measurements for IT Racks and computer rooms. This sensor is used for measuring temperature. The design allows for daisy chaining. Up to 7 sensors can be linked together.

Product Specifications

Feature	Values
Indicator	Digital

Additional specifications

Features	Values
Temperature Range	-40°C to + 125°C
Maximum Sensors	8 (1+7)
Accuracy	-25 to 85 °C = +/-0.5°C Nominal
Humidity Range	0 - 100% Relative Humidity
Response Time	8 Seconds in Slow Moving Air @ 25°C
Total Accuracy	+/- 4.5% RH, 0-100% RH Non Condensing @ 25°C

Excel Intelligent PDU Temperature Sensor Kit with 3 m Lead

Item Code: 555-500-100



Standards

Applicable standard	Detail
RoHS-II-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

Part Number	Description
555-500-100	Excel Intelligent PDU Temperature Sensor Kit with 3 m Lead
555-500-200	Excel Intelligent PDU Temperature and Humidity Sensor
555-500-800	Excel Intelligent PDU Door Sensor Kit

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.

