

Excel Encasa 16 Fibre Distribution Point with 4 SCA Connections Black

Item Code: 916-020

excel
without compromise.

FTTx
solutions



✕ Designated splitter area

✕ IP56 rated

✕ Accepts LC quad or SC duplex

✕ Internal/external

✕ UL 94 V-0

✕ RoHS compliant

Product Overview

The Encasa range of fibre distribution points have been designed to fit within the FTTx network. These enclosures can be aerial or wall mounted. Made from 100% virgin UL 94 V-0 rated material, UV stable and are IP56 rated, allowing them to be used in both internal and external applications. This Encasa fibre distribution point accommodates 16 fibres (using LC connections) or 8 fibres (using SC connections).

Flexibility is increased through the option to use the enclosure for traditional splicing of cables with a capacity of 24 fibres and the installation of pre-terminated cables via the split gland cable exit points that accept both flat and round cable. The use of splitters is also possible with mounting positions for up to 4 units found on the underside of the adaptor tray.

Blown fibre installations can also be accommodated, with a dedicated gas seal holder housed within the cable storage area in the base of the enclosure. Each enclosure comes pre-loaded with APC adaptors and splitters.

The splitters are terminated with APC connections on the outgoing end and unterminated on the incoming end as standard. Options are available to have adaptors and standard pigtailed or loaded with adaptors only.

The cable entry points allow for midspan cable installation and for cable to be passed through to feed further enclosures in the network. Integrated fibre management allows 250 µm and 900 µm fibre to be installed, keeping the fibres safe and always maintaining the required bend radius.

Product Specifications

| Feature | Values |
|-------------------|---------|
| Surface mounted | yes |
| Type of connector | LCA/SCA |
| With couplers | yes |

Excel Encasa 16 Fibre Distribution Point with 4 SCA Connections Black

Item Code: 916-020



| | |
|----------------------------|-------------|
| Suitable for type of fibre | Single mode |
| IP-rating | IP56 |
| Ambient temperature | -40...60 °C |
| Width | 155 mm |
| Height | 193 mm |
| Depth | 77 mm |

Additional specifications

| Features | Values |
|---|---|
| Maximum number of fibres | 8 SC or 16 LC |
| Maximum number of splices | 24 |
| Adaptor type | SC simplex or LC quad |
| Maximum number of adaptor positions | 4 |
| IP rating | IP56 (suitable for internal and external installations) |
| UV stable | Yes |
| Material | ABS + PC |
| UL94-V0 | Yes |
| Colour (Other colours available subject to MOQ) | Light Grey (RAL 7035) or black (RAL 9005) |
| Dimensions (mm) | 193 mm H x 155 mm W x 77 mm D |

Splitter Options

| Features | Values |
|-------------------|--------|
| 1:4 plc splitter | Max. 4 |
| 1:8 plc splitter | Max. 2 |
| 1:16 plc splitter | Max. 1 |

Cable Entry and Exit Parameters

| Features | Values |
|-------------------------------------|---------------|
| Number of feeder cable entry points | 2 |
| Midspan capability | Yes |
| Cable diameter | 6 mm to 12 mm |
| Number of drop cable exit points | 16 |
| Cable diameter | 3 mm - 6 mm |

Excel Encasa 16 Fibre Distribution Point with 4 SCA Connections Black

Item Code: 916-020



| | |
|-----------------------------------|--------------|
| Number of rear cable netry points | 1 |
| Cable diameter | 6 mm - 12 mm |

LC and SC/APC Adaptor Specification

| Features | Values |
|---------------------------|-----------------------|
| Insertion loss | < 0.2 dB |
| Durability (500 mating) | < 0.2 dB max increase |
| Operating temperature | -40°C to 80°C |
| Retention force | 200 - 600 grams |
| Alignment sleeve material | Ceramic |
| Flammability rated | UL 94 V-0 |
| Polish type | APC |

Splitter Specification

| Features | Values |
|---|-------------------|
| | 1x4 1x8 1x16 |
| Operating wacelength | 1260 to 1650 |
| Fibre type | G.657.A2 |
| Temperature stability (dB) at -40°C to 85°C | ≤ 0.4 ≤ 0.4 ≤ 0.5 |
| Storage temperature | -40°C to 85°C |
| Return loss | ≥ 55 dB |

Standards

| Applicable standard | Detail |
|---|---|
| RoHS-II/III (2011/65/EU & 2015/863): 2023 | Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III). |
| WFD: 2023 | Compliant to Waste Framework Directive |
| SCIP: 2023 | Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products) |
| POPs (EU) No 2019/1021 | EU Regulation for the restriction of Persistent Organic Pollutants. |

Excel Encasa 16 Fibre Distribution Point with 4 SCA Connections Black

Item Code: 916-020



Part Number Table

| Part Number | Description |
|-------------|---|
| 916-000 | Excel Encasa 16 Fibre Distribution Point with 16 LCA Connections + 4x 1:4 Splitter Black |
| 916-001 | Excel Encasa 16 Fibre Distribution Point with 16 LCA Connections + 4x 1:4 Splitter Grey |
| 916-002 | Excel Encasa 16 Fibre Distribution Point with 16 LCA Connections + 2x 1:8 Splitter Black |
| 916-003 | Excel Encasa 16 Fibre Distribution Point with 16 LCA Connections + 2x 1:8 Splitter Grey |
| 916-004 | Excel Encasa 16 Fibre Distribution Point with 16 LCA Connections + 1x 1:16 Splitter Black |
| 916-005 | Excel Encasa 16 Fibre Distribution Point with 16 LCA Connections + 2x 1:16 Splitter Grey |
| 916-006 | Excel Encasa 16 Fibre Distribution Point with 8 SCA Connections + 1x 1:8 Splitter Black |
| 916-007 | Excel Encasa 16 Fibre Distribution Point with 8 SCA Connections + 1x 1:8 Splitter Grey |
| 916-008 | Excel Encasa 16 Fibre Distribution Point with 8 SCA Connections + 2x 1:4 Splitter Black |
| 916-009 | Excel Encasa 16 Fibre Distribution Point with 8 SCA Connections + 2x 1:4 Splitter Grey |
| 916-010 | Excel Encasa 16 Fibre Distribution Point with 4 LCA Connections Black |
| 916-011 | Excel Encasa 16 Fibre Distribution Point with 4 LCA Connections Grey |
| 916-012 | Excel Encasa 16 Fibre Distribution Point with 8 LCA Connections Black |
| 916-013 | Excel Encasa 16 Fibre Distribution Point with 8 LCA Connections Grey |
| 916-014 | Excel Encasa 16 Fibre Distribution Point with 12 LCA Connections Black |
| 916-015 | Excel Encasa 16 Fibre Distribution Point with 12 LCA Connections Grey |
| 916-016 | Excel Encasa 16 Fibre Distribution Point with 16 LCA Connections Black |
| 916-017 | Excel Encasa 16 Fibre Distribution Point with 16 LCA Connections Grey |
| 916-018 | Excel Encasa 16 Fibre Distribution Point with 2 SCA Connections Black |
| 916-019 | Excel Encasa 16 Fibre Distribution Point with 2 SCA Connections Grey |
| 916-020 | Excel Encasa 16 Fibre Distribution Point with 4 SCA Connections Black |
| 916-021 | Excel Encasa 16 Fibre Distribution Point with 4 SCA Connections Grey |
| 916-022 | Excel Encasa 16 Fibre Distribution Point with 6 SCA Connections Black |
| 916-023 | Excel Encasa 16 Fibre Distribution Point with 6 SCA Connections Grey |

Excel Encasa 16 Fibre Distribution Point with 4 SCA Connections Black

Item Code: 916-020



| | |
|---------|--|
| 916-024 | Excel Encasa 16 Fibre Distribution Point with 8 SCA Connections Black |
| 916-025 | Excel Encasa 16 Fibre Distribution Point with 8 SCA Connections Grey |
| 916-026 | Excel Encasa 16 Fibre Distribution Point with 10 SCA Connections Black |
| 916-046 | Excel Encasa 16 Fibre Distribution Point with 4 LCA Connections + 1x 1:4 Splitter Black |
| 916-047 | Excel Encasa 16 Fibre Distribution Point with 4 LCA Connections + 1x 1:4 Splitter Grey |
| 916-048 | Excel Encasa 16 Fibre Distribution Point with 8 LCA Connections + 2x 1:4 Splitter Black |
| 916-049 | Excel Encasa 16 Fibre Distribution Point with 8 LCA Connections + 2x 1:4 Splitter Grey |
| 916-050 | Excel Encasa 16 Fibre Distribution Point with 12 LCA Connections + 3x 1:4 Splitter Black |
| 916-051 | Excel Encasa 16 Fibre Distribution Point with 12 LCA Connections + 3x 1:4 Splitter Grey |
| 916-052 | Excel Encasa 16 Fibre Distribution Point with 8 LCA Connections + 1x 1:8 Splitter Black |
| 916-053 | Excel Encasa 16 Fibre Distribution Point with 8 LCA Connections + 1x 1:8 Splitter Grey |
| 916-054 | Excel Encasa 16 Fibre Distribution Point with 4 SCA Connections + 1x 1:4 Splitter Black |
| 916-055 | Excel Encasa 16 Fibre Distribution Point with 4 SCA Connections + 1x 1:4 Splitter Grey |
| 916-056 | Excel Encasa 16 Fibre Distribution Point Unloaded Grey |
| 916-077 | Excel Encasa 16 Fibre Distribution Point Unloaded Black |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.