Item Code: 924-011





| X Designated splitter area        |
|-----------------------------------|
| X IP56 rated                      |
| X Accepts LC duplex or SC simplex |
| X Internal/external               |
| X UL 94 V-0                       |

#### **Product Overview**

The Encasa range of fibre distribution points have been designed to fit within the FTTx network. These enclosures can be aerial or wall mounted. Made from 100% virgin UL 94 V-0 rated material, UV stable and are IP56 rated, allowing them to be used in both internal and external applications. This Encasa fibre distribution point accommodates 24 fibres (using LC connections) or 12 fibres (using SC connections).

X RoHS compliant

Flexibility is increased through the option to use the enclosure for traditional splicing of cables with a capacity of 24 fibres and the installation of pre-terminated cables via the split gland cable exit points. The use of splitters is also possible with mounting positions for up to 6 units found on the underside of the adaptor tray. Each enclosure comes pre-loaded with APC adaptors and splitters.

The splitters are terminated with APC connections on the outgoing end and unterminated on the incoming end as standard. Options are available to have adaptors and standard pigtails or loaded with adaptors only.

The cable entry points allow for midspan cable installation and for cable to be passed through to feed further enclosures in the network. Integrated fibre management allows 250  $\mu$ m and 900  $\mu$ m fibre to be installed, keeping the fibres safe and always maintaining the required bend radius.

#### **Product Specifications**

| Feature                    | Values      |
|----------------------------|-------------|
| Surface mounted            | yes         |
| Type of connector          | LCA/SCA     |
| With couplers              | yes         |
| Suitable for type of fibre | Single mode |
| •                          |             |
| IP-rating                  | IP56        |

Item Code: 924-011



| Ambient temperature | -4060 °C |  |
|---------------------|----------|--|
| Width               | 137 mm   |  |
| Height              | 341 mm   |  |
| Depth               | 95 mm    |  |

### **Additional specifications**

| Features  | Values  |
|---|---|
| Maximum number of fibres                        | 12 SC or 24 LC  |
| Maximum number of splices                       | 24  |
| Adaptor type                                    | SC simplex or LC quad                                   |
| Maximum number of adaptor positions             | 12  |
| IP rating                                       | IP56 (suitable for internal and external installations) |
| UV stable                                       | Yes   |
| Material  | ABS + PC  |
| UL94-V0   | Yes   |
| Colour (Other colours available subject to MOQ) | Light Grey (RAL 7035) or black (RAL 9005)               |
| Dimensions (mm)                                 | 341 mm H x 137 mm W x 95 mm D                           |

### **Splicer Options**

| Features         | Values |
|------------------|--------|
| 1:4 plc plitter  | Max. 6 |
| 1:8 plc splitter | Max. 3 |

#### **Cable Entry and Exit Parameters**

| Features                            | Values        |
|-------------------------------------|---------------|
| Number of feeder cable entry points | 4             |
| Midspan capability                  | Yes           |
| Cable diameter                      | 6 mm to 12 mm |
| Number of drop cable exit points    | 24            |
| Cable diameter                      | 3 mm - 6 mm   |

#### LC and SC/APC Adaptor Specification

| Features       | Values   |
|----------------|----------|
| Insertion loss | < 0.2 dB |

Item Code: 924-011



| Durability (500 mating)   | < 0.2 dB max increase |
|---------------------------|-----------------------|
| Operating temperature     | -40°C to 80°C         |
| Retention force           | 200 - 600 grams       |
| Alignment sleeve material | Ceramic               |
| Flammability rated        | UL 94 V-0             |
| Polish type               | APC                   |

### **Splitter Specification**

| Features                                    | Values              |
|---|---------------------|
|   | 1x4 1x8             |
| Operating wacelength                        | 1260 to 1650        |
| Fibre type                                  | G.657.A2            |
| Temperature stability (dB) at -40°C to 85°C | $\leq 0.4 \leq 0.4$ |
| Storage temperature                         | -40°C to 85°C       |
| Return loss                                 | ≥ 55 dB             |

#### **Standards**

| Applicable standard                        | Detail  |
|--|---|
| RoHS-II/-III (2011/65/EU & 2015/863): 2023 | Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III). |
| WFD: 2023                                  | Compliant to Waste Framework Directive  |
| SCIP: 2023                                 | Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)   |
| POPs (EU) No 2019/1021                     | EU Regulation for the restriction of Persistent Organic Pollutants.   |

#### **Part Number Table**

| Part Number | Description  |
|-------------|--|
| 924-000     | Excel Encasa 24 Fibre Distribution Point with 24 LCA Connections + 6x 1:4 Splitter Black |
| 924-001     | Excel Encasa 24 Fibre Distribution Point with 24 LCA Connections + 6x 1:4                |

Item Code: 924-011



|         | Splitter Grey  |
|---------|--|
| 924-002 | Excel Encasa 24 Fibre Distribution Point with 24 LCA Connections $+ 3x 1:8$ Splitter Black       |
| 924-003 | Excel Encasa 24 Fibre Distribution Point with 24 LCA Connections $+\ 3x\ 1:8$ Splitter Grey      |
| 924-004 | Excel Encasa 24 Fibre Distribution Point with 12 SCA Connections $+$ 3x 1:4 Splitter Black       |
| 924-005 | Excel Encasa 24 Fibre Distribution Point with 12 SCA Connections $+ 3x 1:4$ Splitter Grey        |
| 924-006 | Excel Encasa 24 Fibre Distribution Point with 4 LCA Connections Black                            |
| 924-007 | Excel Encasa 24 Fibre Distribution Point with 4 LCA Connections Grey                             |
| 924-008 | Excel Encasa 24 Fibre Distribution Point with 8 LCA Connections Black                            |
| 924-009 | Excel Encasa 24 Fibre Distribution Point with 8 LCA Connections Grey                             |
| 924-010 | Excel Encasa 24 Fibre Distribution Point with 12 LCA Connections Black                           |
| 924-011 | Excel Encasa 24 Fibre Distribution Point with 12 LCA Connections Grey                            |
| 924-012 | Excel Encasa 24 Fibre Distribution Point with 16 LCA Connections Black                           |
| 924-013 | Excel Encasa 24 Fibre Distribution Point with 16 LCA Connections Grey                            |
| 924-014 | Excel Encasa 24 Fibre Distribution Point with 24 LCA Connections Black                           |
| 924-015 | Excel Encasa 24 Fibre Distribution Point with 24 LCA Connections Grey                            |
| 924-026 | Excel Encasa 24 Fibre Distribution Point with 4 LCA Connections + $1 \times 1$ :4 Splitter Black |
| 924-027 | Excel Encasa 24 Fibre Distribution Point with 4 LCA Connections $+\ 1x\ 1:4$ Splitter Grey       |
| 924-028 | Excel Encasa 24 Fibre Distribution Point with 8 LCA Connections + $2x$ 1:4 Splitter Black        |
| 924-029 | Excel Encasa 24 Fibre Distribution Point with 8 LCA Connections $+ 2x 1:4$ Splitter Grey         |
| 924-030 | Excel Encasa 24 Fibre Distribution Point with 12 LCA Connections + $3x$ 1:4 Splitter Black       |
| 924-031 | Excel Encasa 24 Fibre Distribution Point with 12 LCA Connections $+ 3x 1:4$ Splitter Grey        |
| 924-032 | Excel Encasa 24 Fibre Distribution Point with 16 LCA Connections + 4x 1:4 Splitter Black         |
| 924-033 | Excel Encasa 24 Fibre Distribution Point with 16 LCA Connections + 4x 1:4 Splitter Grey          |
| 924-035 | Excel Encasa 24 Fibre Distribution Point with 8 LCA Connections + $1 \times 1:8$ Splitter Grey   |
| 924-036 | Excel Encasa 24 Fibre Distribution Point with 16 LCA Connections + 2x 1:8                        |
|         |  |

Item Code: 924-011



|         | Splitter Black  |
|---------|---|
| 924-037 | Excel Encasa 24 Fibre Distribution Point with 16 LCA Connections $+\ 2x\ 1:8$ Splitter Grey     |
| 924-053 | Excel Encasa 24 Fibre Distribution Point with 4 SCA Connections Black                           |
| 924-054 | Excel Encasa 24 Fibre Distribution Point with 4 SCA Connections Grey                            |
| 924-055 | Excel Encasa 24 Fibre Distribution Point with 8 SCA Connections Black                           |
| 924-056 | Excel Encasa 24 Fibre Distribution Point with 8 SCA Connections Grey                            |
| 924-057 | Excel Encasa 24 Fibre Distribution Point with 12 SCA Connections Black                          |
| 924-058 | Excel Encasa 24 Fibre Distribution Point with 12 SCA Connections Grey                           |
| 924-059 | Excel Encasa 24 Fibre Distribution Point with 4 SCA Connections + 4 Pigtails Black              |
| 924-060 | Excel Encasa 24 Fibre Distribution Point with 4 SCA Connections + 4 Pigtails Grey               |
| 924-061 | Excel Encasa 24 Fibre Distribution Point with 8 SCA Connections + 8 Pigtails Black              |
| 924-062 | Excel Encasa 24 Fibre Distribution Point with 8 SCA Connections + 8 Pigtails Grey               |
| 924-063 | Excel Encasa 24 Fibre Distribution Point with 12 SCA Connections $+$ 12 Pigtails Black          |
| 924-064 | Excel Encasa 24 Fibre Distribution Point with 12 SCA Connections $+$ 12 Pigtails Grey           |
| 924-065 | Excel Encasa 24 Fibre Distribution Point with 4 SCA Connections + $1 \times 1:4$ Splitter Black |
| 924-066 | Excel Encasa 24 Fibre Distribution Point with 4 SCA Connections + $1 \times 1:4$ Splitter Grey  |
| 924-067 | Excel Encasa 24 Fibre Distribution Point with 8 SCA Connections $+$ 2x 1:4 Splitter Black       |
| 924-068 | Excel Encasa 24 Fibre Distribution Point with 8 SCA Connections $+\ 2x\ 1:4$ Splitter Grey      |
| 924-069 | Excel Encasa 24 Fibre Distribution Point with 8 SCA Connections + $1 \times 1:8$ Splitter Black |
| 924-070 | Excel Encasa 24 Fibre Distribution Point with 8 SCA Connections + $1 \times 1:8$ Splitter Grey  |
| 924-081 | Excel Encasa 24 Fibre Distribution Point with 16 LCA Connections $+\ 1x\ 1:16$ Splitter Grey    |
|         |   |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.