

# Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections Grey

Item Code: 936-008



✕ Designated splitter area

✕ IP56 rated

✕ Accepts LC Duplex or SC Simplex

✕ Internal/external

✕ UL 94-V0

✕ RoHS compliant

## Product Overview

The Encasa range of fibre distribution points has been meticulously designed to seamlessly integrate into the FTTx network. These enclosures can be aerially or wall-mounted. Crafted from 100% virgin UL 94-V0 rated material, UV stable, and boasting an IP56 rating, they excel in both internal and external applications.

This Encasa fibre distribution point accommodates 36 fibres (using LC connections) or 18 fibres (using SC connections). Flexibility is enhanced through the option to utilize the enclosure for traditional cable splicing with a capacity of 36 fibres and for the installation of pre-terminated cables via the split gland cable exit points.

The use of splitters is also supported, with mounting positions for up to 8 units located on the underside of the adaptor tray. Each enclosure comes pre-loaded with APC adaptors and splitters. The splitters are terminated with APC connections on the outgoing end and left unterminated on the incoming end as standard.

Options are available to be loaded with adaptors and standard pigtails or with adaptors only. The cable entry points allow for midspan cable installation and for cables to be passed through to provide feed to additional enclosures in the network.

Integrated fibre management allows for the installation of 250 µm and 900 µm fibres, ensuring the safety of the fibres and maintaining the required bend radius.

## Product Specifications

| Feature                    | Values      |
|----------------------------|-------------|
| Surface mounted            | yes         |
| Type of connector          | LCA/SCA     |
| With couplers              | yes         |
| Suitable for type of fibre | Single mode |

# Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections Grey

Item Code: 936-008



|                     |             |
|---------------------|-------------|
| IP-rating           | IP56        |
| Ambient temperature | -40...60 °C |
| Width               | 148 mm      |
| Height              | 320 mm      |
| Depth               | 102 mm      |

## Additional specifications

| Features  | Values  |
|---|---|
| Maximum number of fibres                        | 36  |
| Maximum number of splices                       | 36  |
| Adaptor type                                    | SC simplex or LC duplex                                 |
| Maximum number of adaptor positions             | 18  |
| IP rating                                       | IP56 (suitable for internal and external installations) |
| UV stable                                       | Yes   |
| Material  | ABS + PC  |
| UL94-V0   | Yes   |
| Colour (Other colours available subject to MOQ) | Light grey (RAL 7035) or black (RAL 9005)               |
| Dimensions (mm)                                 | 320 mm H x 148 mm W x 102 mm D                          |

## Splitter Options

| Features          | Values |
|-------------------|--------|
| 1:4 plc splitter  | Max. 8 |
| 1:8 plc splitter  | Max. 8 |
| 1:16 plc splitter | Max. 2 |
| 1:32 plc splitter | Max. 1 |

## Cable Entry and Exit Parameters

| Features                            | Values       |
|-------------------------------------|--------------|
| Number of feeder cable entry points | 4            |
| Midspan capability                  | Yes          |
| Cable diameter                      | 6 mm - 12 mm |
| Number of drop cable exit points    | 36           |
| Cable diameter                      | 3 mm - 6 mm  |

## LC and SC /APC Adaptor Specification

| Features                  | Values                |
|---------------------------|-----------------------|
| Insertion loss            | < 0.2 dB              |
| Durability (500 mating)   | < 0.2 dB max increase |
| Operating temperature     | -40°C to 80°C         |
| Retention force           | 200 - 600 grams       |
| Alignment sleeve material | Ceramic               |
| Flammability rated        | UL 94 V-0             |
| Polish type               | APC                   |

## Splitter Specification

| Features                                    | Values        |
|---|---------------|
| Operating wacelength                        | 1260 to 1650  |
| Fibre type                                  | G.657.A2      |
| Temperature stability (dB) at -40°C to 85°C | ≤ 0.4         |
| Storage temperature                         | -40°C to 85°C |
| Return loss                                 | ≥ 55 dB       |

## Standards

| Applicable standard                       | Detail  |
|---|---|
| RoHS-II/III (2011/65/EU & 2015/863): 2023 | Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III). |
| WFD: 2023                                 | Compliant to Waste Framework Directive  |
| SCIP: 2023                                | Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)   |
| POPs (EU) No 2019/1021                    | EU Regulation for the restriction of Persistent Organic Pollutants.   |

# Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections Grey

Item Code: 936-008



## Part Number Table

| Part Number | Description  |
|-------------|--|
| 936-000     | Excel Encasa 36 Fibre Distribution Point Unloaded Black                                  |
| 936-001     | Excel Encasa 36 Fibre Distribution Point with 4 LCA Connections Black                    |
| 936-002     | Excel Encasa 36 Fibre Distribution Point with 4 LCA Connections Grey                     |
| 936-003     | Excel Encasa 36 Fibre Distribution Point with 8 LCA Connections Black                    |
| 936-004     | Excel Encasa 36 Fibre Distribution Point with 8 LCA Connections Grey                     |
| 936-005     | Excel Encasa 36 Fibre Distribution Point with 12 LCA Connections Black                   |
| 936-006     | Excel Encasa 36 Fibre Distribution Point with 12 LCA Connections Grey                    |
| 936-007     | Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections Black                   |
| 936-008     | Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections Grey                    |
| 936-009     | Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections Black                   |
| 936-010     | Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections Grey                    |
| 936-011     | Excel Encasa 36 Fibre Distribution Point with 36 LCA Connections Black                   |
| 936-012     | Excel Encasa 36 Fibre Distribution Point with 36 LCA Connections Grey                    |
| 936-025     | Excel Encasa 36 Fibre Distribution Point with 4 LCA Connections + 1x 1:4 Splitter Black  |
| 936-026     | Excel Encasa 36 Fibre Distribution Point with 4 LCA Connections + 1x 1:4 Splitter Grey   |
| 936-027     | Excel Encasa 36 Fibre Distribution Point with 8 LCA Connections + 2x 1:4 Splitter Black  |
| 936-028     | Excel Encasa 36 Fibre Distribution Point with 8 LCA Connections + 2x 1:4 Splitter Grey   |
| 936-029     | Excel Encasa 36 Fibre Distribution Point with 8 LCA Connections + 1x 1:8 Splitter Black  |
| 936-030     | Excel Encasa 36 Fibre Distribution Point with 8 LCA Connections + 1x 1:8 Splitter Grey   |
| 936-031     | Excel Encasa 36 Fibre Distribution Point with 12 LCA Connections + 3x 1:4 Splitter Black |
| 936-032     | Excel Encasa 36 Fibre Distribution Point with 12 LCA Connections + 3x 1:4 Splitter Grey  |
| 936-033     | Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections + 4x 1:4 Splitter Black |
| 936-034     | Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections + 4x 1:4 Splitter Grey  |
| 936-035     | Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections + 2x 1:8 Splitter Black |

# Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections Grey

Item Code: 936-008



|         |   |
|---------|---|
| 936-036 | Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections + 2x 1:8 Splitter Grey   |
| 936-037 | Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections + 1x 1:16 Splitter Black |
| 936-038 | Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections + 1x 1:16 Splitter Grey  |
| 936-039 | Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections + 8x 1:4 Splitter Black  |
| 936-040 | Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections + 8x 1:4 Splitter Grey   |
| 936-041 | Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections + 2x 1:16 Splitter Black |
| 936-042 | Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections + 2x 1:16 Splitter Grey  |
| 936-043 | Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections + 1x 1:32 Splitter Black |
| 936-044 | Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections + 1x 1:32 Splitter Grey  |
| 936-065 | Excel Encasa 36 Fibre Distribution Point with 4 SCA Connections Black                     |
| 936-066 | Excel Encasa 36 Fibre Distribution Point with 4 SCA Connections Grey                      |
| 936-067 | Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections Black                     |
| 936-068 | Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections Grey                      |
| 936-069 | Excel Encasa 36 Fibre Distribution Point with 12 SCA Connections Black                    |
| 936-070 | Excel Encasa 36 Fibre Distribution Point with 12 SCA Connections Grey                     |
| 936-071 | Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections Black                    |
| 936-072 | Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections Grey                     |
| 936-081 | Excel Encasa 36 Fibre Distribution Point with 4 SCA Connections + 1x 1:4 Splitter Black   |
| 936-082 | Excel Encasa 36 Fibre Distribution Point with 4 SCA Connections + 1x 1:4 Splitter Grey    |
| 936-083 | Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections + 2x 1:4 Splitter Black   |
| 936-084 | Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections + 2x 1:4 Splitter Grey    |
| 936-085 | Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections + 1x 1:8 Splitter Black   |
| 936-086 | Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections + 1x 1:8 Splitter Grey    |

# Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections Grey

Item Code: 936-008



|         |   |
|---------|---|
| 936-087 | Excel Encasa 36 Fibre Distribution Point with 12 SCA Connections + 3x 1:4 Splitter Black  |
| 936-088 | Excel Encasa 36 Fibre Distribution Point with 12 SCA Connections + 3x 1:4 Splitter Grey   |
| 936-089 | Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + 4x 1:4 Splitter Black  |
| 936-090 | Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + 4x 1:4 Splitter Grey   |
| 936-091 | Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + 2x 1:8 Splitter Black  |
| 936-092 | Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + 2x 1:8 Splitter Grey   |
| 936-093 | Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + 1x 1:16 Splitter Black |
| 936-094 | Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + 1x 1:16 Splitter Grey  |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at [sales@excel-networking.com](mailto:sales@excel-networking.com)



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.