Item Code: 936-039








X Designated splitter a	rea
-------------------------	-----

$\mathbf{X}$	IP56	rated

X	Accepts	LC [	Dupl	ex or	'SC S	impl	ex

<b>N</b>		
-X	Interna	l/externa



#### **Product Overview**

The Encasa range of fibre distribution points has been meticulously designed to seamlessly integrate into the FTTx network. These enclosures can be aerially or wall-mounted. Crafted from 100% virgin UL 94-V0 rated material, UV stable, and boasting an IP56 rating, they excel in both internal and external applications.

This Encasa fibre distribution point accommodates 36 fibres (using LC connections) or 18 fibres (using SC connections). Flexibility is enhanced through the option to utilize the enclosure for traditional cable splicing with a capacity of 36 fibres and for the installation of pre-terminated cables via the split gland cable exit points.

The use of splitters is also supported, with mounting positions for up to 8 units located on the underside of the adaptor tray. Each enclosure comes pre-loaded with APC adaptors and splitters. The splitters are terminated with APC connections on the outgoing end and left unterminated on the incoming end as standard.

Options are available to be loaded with adaptors and standard pigtails or with adaptors only. The cable entry points allow for midspan cable installation and for cables to be passed through to provide feed to additional enclosures in the network.

Integrated fibre management allows for the installation of 250  $\mu m$  and 900  $\mu m$  fibres, ensuring the safety of the fibres and maintaining the required bend radius.

#### **Product Specifications**

Feature	Values
Surface mounted	yes
Type of connector	LCA/SCA
With couplers	yes
Suitable for type of fibre	Single mode

Item Code: 936-039



IP-rating	IP56
Ambient temperature	-4060 °C
Width	148 mm
Height	320 mm
Depth	102 mm

### **Additional specifications**

Features	Values
Maximum number of fibres	36
Maximum number of splices	36
Adaptor type	SC simplex or LC duplex
Maximum number of adaptor positions	18
IP rating	IP56 (suitable for internal and external installations)
UV stable	Yes
Material	ABS + PC
UL94-V0	Yes
Colour (Other colours available subject to MOQ)	Light grey (RAL 7035) or black (RAL 9005)
Dimensions (mm)	320 mm H x 148 mm W x 102 mm D

#### **Splitter Options**

Features	Values
1:4 plc splitter	Max. 8
1:8 plc splitter	Max. 8
1:16 plc splitter	Max. 2
1:32 plc splitter	Max. 1

### **Cable Entry and Exit Parameters**

Features	Values
Number of feeder cable entry points	4
Midspan capability	Yes
Cable diameter	6 mm - 12 mm
Number of drop cable exit points	36
Cable diameter	3 mm - 6 mm

Item Code: 936-039



#### LC and SC /APC Adaptor Specification

Features	Values
Insertion loss	< 0.2 dB
Durability (500 mating)	< 0.2 dB max increase
Operating temperature	-40°C to 80°C
Retention force	200 - 600 grams
Alignment sleeve material	Ceramic
Flammability rated	UL 94 V-0
Polish type	APC

### **Splitter Specification**

Features	Values
Operating wacelength	1260 to 1650
Fibre type	G.657.A2
Temperature stability (dB) at -40°C to 85°C	≤ 0.4
Storage temperature	-40°C to 85°C
Return loss	≥ 55 dB

#### **Standards**

Applicable standard	Detail
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

Item Code: 936-039



#### **Part Number Table**

ore Distribution Point Unloaded Black ore Distribution Point with 4 LCA Connections Black ore Distribution Point with 4 LCA Connections Grey ore Distribution Point with 8 LCA Connections Black ore Distribution Point with 8 LCA Connections Grey ore Distribution Point with 12 LCA Connections Black ore Distribution Point with 12 LCA Connections Grey
ore Distribution Point with 4 LCA Connections Grey ore Distribution Point with 8 LCA Connections Black ore Distribution Point with 8 LCA Connections Grey ore Distribution Point with 12 LCA Connections Black
ore Distribution Point with 8 LCA Connections Black ore Distribution Point with 8 LCA Connections Grey ore Distribution Point with 12 LCA Connections Black
ore Distribution Point with 8 LCA Connections Grey ore Distribution Point with 12 LCA Connections Black
ore Distribution Point with 12 LCA Connections Black
ore Distribution Point with 12 LCA Connections Grey
ore Distribution Point with 16 LCA Connections Black
ore Distribution Point with 16 LCA Connections Grey
ore Distribution Point with 32 LCA Connections Black
ore Distribution Point with 32 LCA Connections Grey
ore Distribution Point with 36 LCA Connections Black
ore Distribution Point with 36 LCA Connections Grey
ore Distribution Point with 4 LCA Connections + 1x 1:4
ore Distribution Point with 4 LCA Connections + 1x 1:4
ore Distribution Point with 8 LCA Connections + 2x 1:4
ore Distribution Point with 8 LCA Connections + 2x 1:4
ore Distribution Point with 8 LCA Connections + 1x 1:8
ore Distribution Point with 8 LCA Connections + 1x 1:8
ore Distribution Point with 12 LCA Connections + 3x 1:4
ore Distribution Point with 12 LCA Connections + 3x 1:4
ore Distribution Point with 16 LCA Connections + 4x 1:4
ore Distribution Point with 16 LCA Connections + 4x 1:4
ore Distribution Point with 16 LCA Connections + 2x 1:8

Item Code: 936-039



936-036	Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections + $2x$ 1:8 Splitter Grey
936-037	Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections + $1 \times 1:16$ Splitter Black
936-038	Excel Encasa 36 Fibre Distribution Point with 16 LCA Connections + $1 \times 1:16$ Splitter Grey
936-039	Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections + 8x 1:4 Splitter Black
936-040	Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections $+\ 8x\ 1:4$ Splitter Grey
936-041	Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections + $2x 1:16$ Splitter Black
936-042	Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections + $2x 1:16$ Splitter Grey
936-043	Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections + $1 \times 1:32$ Splitter Black
936-044	Excel Encasa 36 Fibre Distribution Point with 32 LCA Connections + $1 \times 1:32$ Splitter Grey
936-065	Excel Encasa 36 Fibre Distribution Point with 4 SCA Connections Black
936-066	Excel Encasa 36 Fibre Distribution Point with 4 SCA Connections Grey
936-067	Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections Black
936-068	Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections Grey
936-069	Excel Encasa 36 Fibre Distribution Point with 12 SCA Connections Black
936-070	Excel Encasa 36 Fibre Distribution Point with 12 SCA Connections Grey
936-071	Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections Black
936-072	Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections Grey
936-081	Excel Encasa 36 Fibre Distribution Point with 4 SCA Connections + $1 \times 1:4$ Splitter Black
936-082	Excel Encasa 36 Fibre Distribution Point with 4 SCA Connections + $1 \times 1:4$ Splitter Grey
936-083	Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections + 2x 1:4 Splitter Black
936-084	Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections + $2x 1:4$ Splitter Grey
936-085	Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections + $1 \times 1:8$ Splitter Black
936-086	Excel Encasa 36 Fibre Distribution Point with 8 SCA Connections + $1 \times 1:8$ Splitter Grey

Item Code: 936-039



936-087	Excel Encasa 36 Fibre Distribution Point with 12 SCA Connections + $3 \times 1:4$ Splitter Black
936-088	Excel Encasa 36 Fibre Distribution Point with 12 SCA Connections $+$ 3x 1:4 Splitter Grey
936-089	Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + $4 \times 1:4$ Splitter Black
936-090	Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + $4 \times 1:4$ Splitter Grey
936-091	Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + $2 \times 1:8$ Splitter Black
936-092	Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + $2 \times 1:8$ Splitter Grey
936-093	Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + $1 \times 1:16$ Splitter Black
936-094	Excel Encasa 36 Fibre Distribution Point with 16 SCA Connections + $1 \times 1:16$ Splitter Grey

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

