


Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 3 m Red

Item Code: BBS003MPLRD

excel
without compromise.



Cat5e compliant

Foil tape screen with LSOH outer sheath

Independently verified, T568B wiring

Supports Gigabit ethernet

Choice of colours, individually packaged

Blade style 'slimline' moulded strain relief boot with clip protector

CIBSE TM65 Embodied Carbon: 0.551 kg CO2e

Product Overview

Excel Category 5e F/UTP Patch Leads are manufactured and tested to ISO11801 Category 5e and EIA/TIA 568 standards.

Each cable consists of 8 colour coded stranded conductors twisted together to form 4 pairs with varying lay lengths. Cables are fitted with plastic strain relief boots, for applications that may require continuous patching or a degree of stress relief applied.

Product Specifications

Feature	Values
Cable type	F/UTP
Category	5E
Length	3 m
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Outer sheath colour	Red
Strain relief boot	Moulded-on
Lockable	no


Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 3 m Red

Item Code: BBS003MPLRD

excel
without compromise.

Strain relief boot colour	Red
Flame retardant version	yes
Cable construction	1x4
AWG-size	26
Pin assignment	1:1

Product drawing



- ① 4 pair individually foil screen LSOH cable
- ② RJ45 connector with 50µm gold plated staggered pins
- ③ Slimline blade style strain relief boot

Standards

Applicable standard	Detail
ISO/IEC 11801-1:2017	Information technology - Generic cabling for customer premises: Part 1 General Requirements
EN 50173-1:2018	Information technology. Generic cabling systems - General requirements
ANSI/TIA 568-2.D	Balanced Twisted-Pair Telecommunications Cabling and Components Standards
IEC 61156-5:2009+AMD1:2012 CSV	Multicore and symmetrical pair/quad cables for digital communications - Part 5: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Horizontal floor wiring - Sectional specification
IEC 60332-1-2:2004	Tests on electric and optical fibre cables under fire conditions. Test for vertical flame propagation for a single

Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 3 m Red

Item Code: BBS003MPLRD



insulated wire or cable. Procedure for 1 kW pre-mixed flame

EN 50399:2011+A1:2016

Common test methods for cables under fire conditions. Heat release and smoke production measurement on cables during flame spread test. Test apparatus, procedures, results

IEC 61034-2:2005+A1:2013

Measurement of smoke density of cables burning under defined conditions - Part 2: Test procedure and requirements

Directive 2011/65/EU (RoHS II)

Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).

Directive (EU) 2015/863 (RoHS III)

Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.

Directive 2008/98/EC (WFD)

Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).

ECHA SCIP Database

Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.

Regulation (EU) 2019/1021 (POPs)

EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).

UK SI 2012 No. 3032

The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

Part Number Table

Part Number	Description
BBS0.2MPLGE	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 0.2 m Grey
BBS0.5MPLGE	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 0.5 m Grey
BBS001MPLBU	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 1 m Blue
BBS001MPLGE	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 1 m Grey
BBS001MPLGN	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 1m Green
BBS001MPLRD	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 1 m Red

Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 3 m Red

Item Code: BBS003MPLRD



BBS002MPLGE	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 2 m Grey
BBS003MPLBU	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 3m Blue
BBS003MPLGE	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 3 m Grey
BBS003MPLGN	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 3 m Green
BBS003MPLRD	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 3 m Red
BBS003MPLYW	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 3m Yellow
BBS005MPLGE	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 5 m Grey
BBS007MPLGE	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 7 m Grey
BBS010MPLGE	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 10 m Grey
BBS150MPLGE	Excel Cat5e Patch Lead F/UTP Shielded LSOH Blade Booted 15m Grey

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.