

Excel 4 Way Horizontal PDU 4x UK Socket Passive 32A IEC 60309 Plug LED

Item Code: D32-4H-EXL



- Comprehensive choice of sockets
- Standard 3 m power lead with 32 Amp plug
- Horizontal and vertical options available
- Fully shrouded switch
- LED indicator to confirm power to the unit

Product Overview

Excel professional grade power distribution units (PDUs) are designed for installation and use within 19" networking racks and enclosures. Each unit is loaded with up to 12 sockets, which are housed in a high quality aluminium extruded housing.

Product Specifications

| Feature | Values |
|----------------------------------|--------------------------------|
| Mounting dimension | 19 inch |
| Mounting direction | Horizontal |
| Electrical connection | Connecting cord with plug |
| Type of electric plug connection | 32 Amp - EN6039 Style (BS4343) |
| Cable length | 3 m |
| Number of UK BS1363 sockets | 4 |
| Number of rack units (RU) | 2 |
| Width | 482.6 mm |
| Height | 62 mm |
| Depth | 45 mm |
| Supply voltage | 250 V |
| Surge Protected | no |
| Switchable | no |
| With LED indication | yes |

Item Code: D32-4H-EXL



yes


| Features | Values |
|---------------------------------------|-------------------|
| Rated Voltage | 250 V AC 50/60 Hz |
| Rated current | 32A |
| Maximum power | 8000 W |
| Insulation Resistance | ≥5MΩ |
| Fire resistance | Flame retardant |
| Operating temperature | -10℃~+45℃ |
| Relative humidity | 0%~90% |
| Cable entry (horizontal orientation) | Left |
| Cable entry (vertical orientation) | Top |
| Socket angle (horizontal orientation) | 90° |
| Socket angle (vertical orientation) | 45° |
| Master Circuit Breaker | NO |
| Master Switch | No |
| Housing colour | Silver |
| Housing material | Aluminum |

Excel 4 Way Horizontal PDU 4x UK Socket Passive
32A IEC 60309 Plug LED

Item Code: D32-4H-EXL



Product drawing



Included accessories

| Accessories | Quantity |
|-----------------|----------|
| M6 x 4 fixings | x4 |
| user manual | x1 |
| 6mm earth cable | x1 |

Standards

| Applicable standard | Detail |
|--|---|
| RoHS-II/-III (2011/65/EU & 2015/863): 2023 | Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III). |
| BS 1363-2:1995 | 13 A plugs, socket-outlets, adaptors and connection units. Specification for 13 A switched and unswitched socket-outlets |
| BS 4343:1992 | Plugs, socket-outlets and couplers for industrial purposes |
| BS EN 60309-1:1999+AMD1:2005+AMD2:2012 CSV | Plugs, socket-outlets and couplers for industrial purposes - Part 1: General requirements |
| BS EN 60309-2:1999+AMD1:2005+AMD2:2012 CSV | Plugs, socket-outlets and couplers for industrial purposes - Part 2: Dimensional interchangeability requirements for |

Excel 4 Way Horizontal PDU 4x UK Socket Passive 32A IEC 60309 Plug LED

Item Code: D32-4H-EXL



pin and contact-tube accessories

WFD: 2023

Compliant to Waste Framework Directive

SCIP: 2023

Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)

POPs (EU) No 2019/1021

EU Regulation for the restriction of Persistent Organic Pollutants.

Part Number Table

| Part Number | Description |
|-------------|--|
| D32-10-EXL | Excel 10 Way Vertical PDU 10x UK Socket Passive 32A IEC 60309 Plug LED |
| D32-12-EXL | Excel 12 Way Vertical PDU 12x UK Socket Passive 32A IEC 60309 Plug LED |
| D32-4H-EXL | Excel 4 Way Horizontal PDU 4x UK Socket Passive 32A IEC 60309 Plug LED |
| D32-6H-EXL | Excel 6 Way Horizontal PDU 6x UK Socket Passive 32A IEC 60309 Plug LED |
| D32-8-EXL | Excel 8 Way Vertical PDU 8x UK Socket Passive 32A IEC 60309 Plug LED |

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

Contact us at sales@excel-networking.com



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.