Item Code: TC010PE1W-LSF











- X Available in 10/20/25/32/40/50/100-Pair
- X Choice of reel sizes
- X Cut to length service above 20 Pai
- X LSF outer sheath
- 25 Year system warranty
- X Euroclass Eca
- X CIBSE TM65 Embodied Carbon: 49.930 kg CO2e

#### **Product Overview**

Excel multipair internal telephone cables are manufactured in accordance with BT type CW1308. These cores are twisted into pairs and the required number are sheathed together to form the cable. Groups of pairs are bundled together for ease of identification. An earth conductor of 1.38mm plain copper is included.

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

#### **Product Specifications**

Feature	Values
Diameter of conductor	0.5 mm
Conductor category	Class $1 = solid$
Total number of cores	20
Stranding element	Pairs
Core insulation	Polyvinyl chloride (PVC)
Core identification	Colour + rings
Overall screening	None
Pair grouping identification	Bundles and layers

Item Code: TC010PE1W-LSF



Conductor screening	None
Protective sheath	None
Outer sheath material	Polyvinyl chloride (PVC)
Outer sheath colour	White
Flame retardant according to IEC 60332-1-2	yes
Reaction-to-fire class according to EN 13501-6	Eca
Outer diameter approx.	8.4 mm
Category	Voice

### **Additional specifications**

Features	Values
Conductor Diameter	0.50 mm Nominal
Insulation (up to 25 Pairs)	0.85 +/- 0.005 mm
Insulation (50-100 Pairs)	1.2 +/- 0.005 mm
Insulation (200 Pairs)	2.0 +/- 0.005 mm
Elongation	18 to 24 %.
Spark Test	4.5 KVDC
Conductor Resistance	97.80 ohms / Km at 20 deg. C
Capacitance Unbalance P to P	500 pF / 500m

#### **Binder colour scheme**

Cables	50 Pair	100 Pair	200 Pair
Centre layer	5 x 10 Pairs	1 x 20 Pairs	
First Layer	Orange (10p)	8 x 10 Pairs	
Unit Binder Colours	White (10p)	Orange (20p)	White/Blue (12p)
	White (10p)	Orange (10p)	White/Blue (13p)
	White (10p)	White (10p)	White/Orange (12p)
	Orange (10p)	White (10p)	White/Orange (13p)
		White (10p)	White/Green (25p)
		White (10p)	White/Brown (25p)
		White (10p)	White/Slate (25p)

Item Code: TC010PE1W-LSF



White (10p)	Red/Blue (25p)
Green (10p)	Red/Orange (25p)
	Red/Green (25p)

#### Pair colour scheme

Pair	А	В
1	WHITE-blue	BLUE-white
2	WHITE-orange	ORANGE-white
3	WHITE-green	GREEN-white
4	WHITE-brown	BROWN-white
5	WHITE-slate	SLATE-white
6	RED-blue	BLUE-red
7	RED-orange	ORANGE-red
8	RED-green	GREEN-red
9	RED-brown	BROWN-red
10	RED-slate	SLATE-red
11	BLACK-blue	BLUE-black
12	BLACK-orange	ORANGE-black
13	BLACK-green	GREEN-black
14	BLACK-brown	BROWN-black
15	BLACK-slate	SLATE-black
16	YELLOW-blue	BLUE-yellow
17	YELLOW-orange	ORANGE-yellow
18	YELLOW-green	GREEN-yellow
19	YELLOW-brown	BROWN-yellow
20	YELLOW-slate	SLATE-yellow
21	VIOLET - blue	BLUE - violet
22	VIOLET - orange	ORANGE - violet
23	VIOLET - green	GREEN - violet
24	VIOLET - brown	BROWN - violet
25	VIOLET - slate	SLATE - violet

Item Code: TC010PE1W-LSF



### **Earth conductor specifications**

Features	Values
Conductor Diameter	1.38 mm Nominal.
Insulation	2.70 +/- 0.05 mm
Conductor Resistance	12.40 ohms / Km at 20 deg. C
Insulation colour	Cream

#### **Standards**

Applicable standard	Detail
RoHS-II/-III (2011/65/EU & 2015/863): 2023	Our products, demonstrate full adherence to the regulatory stipulations of the EU Directive 2011/65/EU (RoHS-II) and its corresponding delegated directive 2015/863 (RoHS-III).
EN 50575: 2014 + A1: 2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
BS 6746:1990	Specification for PVC insulation and sheath of electric cables
WFD: 2023	Compliant to Waste Framework Directive
SCIP: 2023	Compliant - Does Not Contain Substances of Concern In articles as such or in complex objects (Products)
POPs (EU) No 2019/1021	EU Regulation for the restriction of Persistent Organic Pollutants.

### **Part Number Table**

Part Number	Description
TC010PE1W-LSF	Excel CW1308 10 Pair+Earth Internal Telephone Cable LSF Eca 100 m Reel White
TC020PE1W-LSF	Excel CW1308 20 Pair+Earth Internal Telephone Cable LSF Eca 100 m Reel White
TC020PEW-LSF	Excel CW1308 20 Pair+Earth Internal Telephone Cable LSF Eca Per Metre White
TC025PE1W-LSF	Excel CW1308 25 Pair+Earth Internal Telephone Cable LSF Eca 100 m Reel White
TC025PEW-LSF	Excel CW1308 25 Pair+Earth Internal Telephone Cable LSF Eca Per Metre

Item Code: TC010PE1W-LSF



	White
TC032PEW-LSF	Excel CW1308 32 Pair+Earth Internal Telephone Cable LSF Eca Per Metre White
TC040PEW-LSF	Excel CW1308 40 Pair+Earth Internal Telephone Cable LSF Eca Per Metre White
TC050PE1W-LSF	Excel CW1308 50 Pair+Earth Internal Telephone Cable LSF Eca 100 m Reel White
TC050PE2W-LSF	Excel CW1308 50 Pair+Earth Internal Telephone Cable LSF Eca 200 m Reel White
TC050PEW-LSF	Excel CW1308 50 Pair+Earth Internal Telephone Cable LSF Eca Per Metre White
TC100PEW-LSF	Excel CW1308 100 Pair+Earth Internal Telephone Cable LSF Eca Per Metre White

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.

