


# Excel CW1308B 100 Pair+Earth Internal/External Telephone Cable Dca Per Metre Black

Item Code: TC100PE-INEX

**excel**  
without compromise.



Cut to length

Available in 10/20/25/50/100/200-Pair

LSOH outer sheath

25 Year system warranty

Euroclass Dca-s3-d2-a3

CIBSE TM65 Embodied Carbon: 4.111 kg CO2e

## Product Overview

Excel Multipair internal/external telephone cables are constructed in a similar way to Standard CW1308 but are suitable for Internal and External use for above ground applications only and offers a UV resistant jacket. An earth conductor of 1.38 mm plain copper is included.

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

## Product Specifications

Feature	Values
Conductor surface	Bare
Diameter of conductor	0.5 mm
Conductor category	Class 1 = solid
Total number of cores	200
Stranding element	Pairs
Core insulation	Polyvinyl chloride (PVC)
Core identification	Colour + rings
Overall screening	None
Pair grouping identification	Bundles and layers

# Excel CW1308B 100 Pair+Earth Internal/External Telephone Cable Dca Per Metre Black

Item Code: TC100PE-INEX



Conductor screening	None
Protective sheath	None
Outer sheath material	Copolymer, thermoplastic (LS0H)
Outer sheath colour	Black
Flame retardant according to IEC 60332-1-2	yes
Reaction-to-fire class according to EN 13501-6	Dca
Smoke development class according to EN 13501-6	s3
Euro class flaming droplets/particles according to EN 13501-6	d2
Euro class acidity according to EN 13501-6	a3
Outer diameter approx.	19.64 mm
Category	Voice

## Additional specifications

Features	Values
Conductor Diameter	0.50 mm Nominal
Insulation (up to 25 Pairs)	0.85 +/- 0.005 mm
Insulation (50-100 Pairs)	1.2 +/- 0.005 mm
Insulation (200 Pairs)	2.0 +/- 0.005 mm
Elongation	18 to 24 %.
Spark Test	4.5 KVDC
Conductor Resistance	97.80 ohms / Km at 20 deg. C
Capacitance Unbalance P to P	500 pF / 500m

## Pair colour scheme

Pair	A	B
1	WHITE-blue	BLUE-white
2	WHITE-orange	ORANGE-white
3	WHITE-green	GREEN-white
4	WHITE-brown	BROWN-white
5	WHITE-slate	SLATE-white
6	RED-blue	BLUE-red

# Excel CW1308B 100 Pair+Earth Internal/External Telephone Cable Dca Per Metre Black

Item Code: TC100PE-INEX



7	RED-orange	ORANGE-red
8	RED-green	GREEN-red
9	RED-brown	BROWN-red
10	RED-slate	SLATE-red
11	BLACK-blue	BLUE-black
12	BLACK-orange	ORANGE-black
13	BLACK-green	GREEN-black
14	BLACK-brown	BROWN-black
15	BLACK-slate	SLATE-black
16	YELLOW-blue	BLUE-yellow
17	YELLOW-orange	ORANGE-yellow
18	YELLOW-green	GREEN-yellow
19	YELLOW-brown	BROWN-yellow
20	YELLOW-slate	SLATE-yellow
21	VIOLET - blue	BLUE - violet
22	VIOLET - orange	ORANGE - violet
23	VIOLET - green	GREEN - violet
24	VIOLET - brown	BROWN - violet
25	VIOLET - slate	SLATE - violet

## Earth conductor specifications

Features	Values
Conductor Diameter	1.38 mm Nominal.
Insulation	2.70 +/- 0.05 mm
Conductor Resistance	12.40 ohms / Km at 20 deg. C
Insulation colour	Cream

**Binder colour scheme (50/100 pair)**

Cables	50 Pair	100 Pair
Centre layer	5 x 10 Pairs	1 x 20 Pairs
First Layer	Orange (10p)	8 x 10 Pairs
Unit Binder Colours	White (10p)	Orange (20p)
	White (10p)	Orange (10p)
	White (10p)	White (10p)
	Orange (10p)	White (10p)
		White (10p)
		White (10p)
		White (10p)
		White (10p)
		Green (10p)

**Binder colour scheme (200 pair)**

Cables	200 Pair
Unit Binder Colours	White/Blue (12p)
	White/Blue (13p)
	White/Orange (12p)
	White/Orange (13p)
	White/Green (25p)
	White/Brown (25p)
	White/Slate (25p)
	Red/Blue (25p)
	Red/Orange (25p)
	Red/Green (25p)

# Excel CW1308B 100 Pair+Earth Internal/External Telephone Cable Dca Per Metre Black

Item Code: TC100PE-INEX



## Standards

Applicable standard	Detail
Directive 2011/65/EU (RoHS II)	Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment — compliant. Applies within EU member states).
Directive (EU) 2015/863 (RoHS III)	Amending Directive 2011/65/EU to add four phthalates (DEHP, BBP, DBP, DIBP) to Annex II — compliant.
EN 50575: 2014 + A1: 2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
BS 6746:1990	Specification for PVC insulation and sheath of electric cables
Directive 2008/98/EC (WFD)	Waste Framework Directive — compliant. Implemented in the UK through the Waste (England and Wales) Regulations 2011 (SI 2011 No. 988).
ECHA SCIP Database	Compliant; product does not contain SVHCs (Substances of Very High Concern) as defined under REACH Article 33(1). Submission obligations met under EU REACH and UK REACH.
Regulation (EU) 2019/1021 (POPs)	EU Regulation on Persistent Organic Pollutants — compliant. For Great Britain, compliance is aligned with the Persistent Organic Pollutants (Amendment) (EU Exit) Regulations 2020 (SI 2020 No. 1355).
UK SI 2012 No. 3032	The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012 (UK RoHS) — compliant for Great Britain. Retained EU law, as amended by the Product Safety and Metrology (Amendment etc.) (EU Exit) Regulations 2019.

## Part Number Table

Part Number	Description
TC010PE-INEX	Excel CW1308B 10 Pair+Earth Internal/External Telephone Cable Dca Per Metre Black
TC020PE-INEX	Excel CW1308B 20 Pair+Earth Internal/External Telephone Cable Dca Per Metre Black
TC025PE-INEX	Excel CW1308B 25 Pair+Earth Internal/External Telephone Cable Dca Per Metre Black
TC050PE-INEX	Excel CW1308B 50 Pair+Earth Internal/External Telephone Cable Dca Per Metre Black
TC100PE-INEX	Excel CW1308B 100 Pair+Earth Internal/External Telephone Cable Dca Per

Excel CW1308B 100 Pair+Earth Internal/External  
Telephone Cable Dca Per Metre Black

Item Code: TC100PE-INEX



Metre Black

TC200PE-INEX

Excel CW1308B 200 Pair+Earth Internal/External Telephone Cable LS0H Dca  
Per Metre Black

Excel is a world class premium performing end to end infrastructure solution designed,  
Manufactured, supported and delivered without compromise.

Contact us at [sales@excel-networking.com](mailto:sales@excel-networking.com)



E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.