Item Code: TCJF5005PB









- X Available in 5/10/20/50/100/200 pairs
- X Cut to length
- X UV and moisture resistant
- X 25 Year system warranty

Product Overview

Excel telecommunication cables are made up from conductors of solid plain copper insulated with cellular (foamed) polyethylene. These conductors are twisted into pairs and the required number of pairs are laid up into units which are identified by coloured tapes. The cables are petroleum jelly filled and sheathed in black polyethylene, and are manufactured in accordance with BT type CW 1128.

The print legend on the cable now includes information regarding the DOP number, Test and Classification of the cable for traceability.

Product Specifications

Feature	Values
Diameter of conductor	0.5 mm
Conductor category	Class 1 = solid
Total number of cores	10
Stranding element	Pairs
Specification core insulation	Polyethylene (PE)
Core identification	Colour + rings
Pair grouping identification	Layers
Longitudinal water blocking cable	yes
Outer sheath material	PE
Outer sheath colour	Black
Flame retardant according to IEC 60332-1-2	no
Low smoke (acc. IEC 61034-2)	no

Item Code: TCJF5005PB



Reaction-to-fire class accor	rding to EN 13501-6	Fca
Outer diameter approx.		8 mm
Category		Voice

Additional specifications

Features	Values
Conductor Diameter	0.50 mm Nominal
Insulation	1.8 +/- 0.005 mm
Elongation	18 to 24 %.
Spark Test	4.5 KVDC
Conductor Resistance	96 ohms / Km at 20 deg. C
Capacitance Unbalance P to P	275 pF / 500m

Pair colour scheme

Pair	Α	В
1	WHITE-blue	BLUE-white
2	WHITE-orange	ORANGE-white
3	WHITE-green	GREEN-white
4	WHITE-brown	BROWN-white
5	WHITE-slate	SLATE-white
6	RED-blue	BLUE-red
7	RED-orange	ORANGE-red
8	RED-green	GREEN-red
9	RED-brown	BROWN-red
10	RED-slate	SLATE-red

Item Code: TCJF5005PB



Binder colour scheme

Cables	20 Pair	50 Pair	100 Pair
Centre layer	2 x 10 Pairs	5 x 10 Pairs	3 x 10 Pairs
First Layer			7 x 10 Pairs
Unit Binder Colours	Blue (10p)	Blue (10p)	Blue (10p)
	Orange (10p)	Orange (10p)	Orange (10p)
		Green (10p)	Green (10p)
		Brown (10p)	Brown (10p)
		Slate (10p)	Slate (10p)
			White (10p)
			Red (10p)
			Black (10p)
			Yellow (10p)
			Violet (10p)

Standards

Applicable standard	Detail
EN 50575: 2014 + A1: 2016	Power, control and communication cables — Cables for general applications in construction works subject to reaction to fire requirements
BS 6746:1990	Specification for PVC insulation and sheath of electric cables

Part Number Table

Part Number	Description
TCJF5005PB	Excel CW1128 5 Pair 1/0.50 mm External Telephone Cable Fca Per Metre Black
TCJF5010PB	Excel CW1128 10 Pair 1/0.50 mm External Telephone Cable Fca Per Metre Black
TCJF5020PB	Excel CW1128 20 Pair 1/0.50 mm External Telephone Cable Fca Per Metre Black
TCJF5050PB	Excel CW1128 50 Pair 1/0.50 mm External Telephone Cable Fca Per Metre Black

Item Code: TCJF5005PB



TCJF5100PB	Excel CW1128 100 Pair 1/0.50 mm External Telephone Cable Fca Per Metre Black
TCJF5200PB	Excel CW1128 200 Pair 1/0.50mm External Telephone Cable Fca Per Metre Black

Excel is a world class premium performing end to end infrastructure solution designed, Manufactured, supported and delivered without compromise.



Contact us at sales@excel-networking.com

E&OE. Excel is a registered trade name of Mayflex Holdings Ltd.